

ピーリング丸棒 SUS304・303

■単位：mm

外径	定尺	m 重量/kg 304・303	ピーリング丸棒	
			304	303
*8	4000	0.399	●	
*9	//	0.505	●	
10	//	0.623	●	
12	//	0.897	●	
13	//	1.05	●	
14	//	1.22	●	
15	//	1.42	●	
16	4000・6000	1.61	●	●
18	//	2.03	●	●
19	//	2.27	●	●
20	//	2.51	●	●
22	//	3.03	●	●
24	//	3.61	●	●
25	//	3.92	●	●
26	6000	4.25	●	●
28	//	4.93	●	●
30	//	5.65	●	●
32	//	6.43	●	●
34	//	7.25	●	●
35	//	7.68	●	●
36	//	8.13	●	●
38	//	9.06	●	●
40	//	10.0	●	●
42	//	11.1	●	●
44	//	12.1	●	●
45	//	12.7	●	●
46	//	13.3	●	●
48	//	14.4	●	●
50	//	15.6	●	●
55	//	18.9	●	●
60	//	22.5	●	●
65	//	26.4	●	●
70	//	30.6	●	●
75	//	35.2	●	●
80	//	40.0	●	●
85	//	45.3	●	●
90	//	50.7	●	●
95	//	56.5	●	●
100	//	62.6	●	●
105	//	69.0	●	
110	//	75.7	●	●
115	//	82.7	●	
120	//	90.1	●	●
125	//	97.7	●	
130	//	106	●	●
135	//	114	●	
140	//	123	●	●
145	//	132	●	
150	//	141	●	●
155	//	152	●	
160	//	161	●	●
170	//	182	●	●
180	//	204	●	●
190	//	227	●	●
200	//	252	●	●

外径	定尺	m 重量/kg 304・303	ピーリング丸棒 304
210	乱尺	277	●
220	//	304	●
230	//	332	●
240	//	362	●
250	//	392	●
260	//	424	●
270	//	457	●
280	//	492	●
290	//	527	●
300	//	564	●
310	//	602	●
320	//	642	●
330	//	682	●
340	//	724	●
350	//	767	●
360	//	812	●
370	//	904	●
380	//	1002	●
390	//	1104	●
400	//	1267	●

*はプラスコンパインド品（冷間仕上）になります。

酸洗丸棒

■単位：mm

外径	定尺	m 重量/kg	304
8	4000	0.399	●
9	//	0.505	●
10	//	0.623	●
12	//	0.897	●
13	//	1.05	●
14	//	1.22	●
15	//	1.42	●
16	//	1.61	●
18	//	2.03	●
19	//	2.27	●
20	//	2.51	●
22	//	3.03	●
24	//	3.61	●
25	//	3.92	●

HL丸棒

■単位：mm

外径	定尺	m 重量/kg	304
8	4000	0.399	HL
9	//	0.505	HL
10	//	0.623	HL
12	//	0.897	HL
13	//	1.05	HL
14	//	1.22	HL
15	//	1.42	HL
16	//	1.61	HL
19	//	2.27	HL
20	//	2.51	HL
22	//	3.03	HL
25	//	3.92	HL

外径許容差基準表

■単位：mm

ピーリング (JIS G4303)				酸洗丸棒 (JIS G4303)	
10mmを超え25mm以下	+0.15、－0	125mmを超え150mm以下	+1.0、－0	15mmを超え25mm以下	+0.15、－0
25mmを超え80mm以下	+0.25、－0	150mmを超え400mm以下	+2.0、－0		
80mmを超え125mm以下	+0.50、－0				

冷間仕上丸棒

引抜丸棒・ミガキ丸棒・センタレス丸棒 SUS304・303・316

■単位：mm

外径	m 重量/kg		引抜丸棒			ミガキ丸棒 (h-9)		センタレス丸棒 (h-7)	
	304・303	316	304	303	316	304	303	304	303
2	0.025		●					●	●
2.5	0.039		●					●	●
3	0.056		●					●	●
3.5	0.076		●					●	●
4	0.100	0.100	●	●	●			●	●
5	0.156	0.157	●	●	●			●	●
6	0.224	0.226	●	●	●			●	●
7	0.305	0.307	●	●	●			●	●
8	0.399	0.401	●	●	●			●	●
9	0.504	0.508	●	●	●			●	●
10	0.623	0.627	●	●	●			●	●
11	0.754	0.758	●	●	●			●	●
12	0.897	0.903	●	●	●			●	●
13	1.05	1.06	●	●	●			●	●
14	1.22	1.23	●	●	●			●	●
15	1.40	1.41	●	●	●			●	●
16	1.59	1.60	●	●	●			●	●
17	1.80	1.81	●	●	●			●	●
18	2.02	2.03	●	●	●			●	●
19	2.25	2.26	●	●	●			●	●
20	2.49	2.51	●	●	●			●	●
22	3.01	3.03	●	●	●			●	●
24	3.59		●	●					
25	3.89	3.92	●	●	●			●	●
26	4.21					●		●	
28	4.88					●	●	●	
30	5.61					●	●	●	●
32	6.38					●	●		
35	7.63					●	●	●	●
38	8.99					●			
40	9.97					●	●	●	●
42	11.0					●			
45	12.6					●	●	●	
50	15.6					●	●	●	
55	18.8					●			
60	22.4					●			
65	26.3					●			
70	30.5					●			
75	35.0					●			
80	39.9					●			
90	50.4					●			
100	62.3					●			

※引抜丸棒：定尺4000mm（一部2000mm・3000mm・5000mmあり）

※ミガキ丸棒：定尺5000mmまたは6000mm（一部4000mmあり）

※センタレス丸棒：定尺SUS304=2000mm、SUS303=2100mm

外径許容差基準表

■単位：mm

引抜丸棒		引抜丸棒 (h-9)		ミガキ丸棒 (h-9)		センタレス丸棒 (h-7)			
2~2.5	+0 -0.04	5~6	+0 -0.030	26~30	+0 -0.052	2~3	+0 -0.010	11~18	+0 -0.018
3~3.5	+0 -0.05	7~10	+0 -0.036	32~50	+0 -0.062	3.5~6	+0 -0.012	19~30	+0 -0.021
4~4.5	+0 -0.06	11~18	+0 -0.043	55~80	+0 -0.074	7~10	+0 -0.015	35~50	+0 -0.025
		19~25	+0 -0.052	90~100	+0 -0.087				

	~3以下	3を超え6以下	6を超え10以下	10を超え18以下	18を超え30以下	30を超え50以下	50を超え80以下
h-7	0、-0.01	0、-0.012	0、-0.015	0、-0.018	0、-0.021	0、-0.025	0、-0.030
h-9	0、-0.025	0、-0.030	0、-0.036	0、-0.043	0、-0.052	0、-0.062	0、-0.074