

フラットバー

HL=HL

4=#400

C=コールド

●=酸洗仕上

フラットバー SUS304・316・316L

■単位：mm

サイズ 厚さ×幅	長さ	kg/P		コールド	HL	#400	スリット ホット	セミ ホット	冷間 圧延	熱間圧延	
		304	316 316L							304	316 316L
2×	6	2,000	0.190	C							
	8	//	0.254	C							
	10	4,000	0.636	C							
	12	//	0.760	C							
	15	//	0.952	C			■				
	20	//	1.27	C			■				
	25	//	1.58	C			■				
	30	//	1.90	C			■				
	32	//	2.03	C			■				
	38	//	2.41				■				
	40	//	2.54	C			■				
	50	//	3.17	C			■				
3×	5	4,000	0.476	C							
	6	//	0.572	C							
	8	//	0.760	C							
	9	//	0.856	C							
	10	//	0.952		HL		■	■			
	12	//	1.14		HL		■	■	●		
	13	//	1.24		HL		■	■			
	15	//	1.43		HL	4	■	■	●		
	16	//	1.52		HL						
	19	//	1.81		HL		■	■	●		
	20	//	1.90	1.92	HL	4	■	■	●	●	*
	22	//	2.09		HL		■	■			
	25	//	2.38	2.39	HL	4	■	■	●	●	
	30	//	2.86	2.87	HL	4	■	■	●	●	
	32	//	3.04	3.06	HL	4	■	■	●	●	
	35	//	3.33		HL		■		●		
	38	//	3.62	3.64	HL	4	■	■	●	●	
	40	//	3.81	3.83	HL	4	■	■	●	●	
	42	//	4.00		HL						
	45	//	4.28		HL		■		●		
	50	//	4.76	4.80	HL	4	■	■	●	●	
	60	//	5.72		HL	4	■	■	●		
	65	//	6.20		HL		■		●		
	75	//	7.12		HL		■	■			
	100	//	9.52		HL		■	■			
	110	//	10.5		HL						
	120	//	11.4		HL						
	125	//	11.9		HL						
	130	//	12.4		HL						
	140	//	13.3		HL						
	150	//	14.3		HL						
4×	9	4,000	1.14	C							
	10	//	1.27		HL						

*SUS316・316L 3×20は冷間圧延になります。

サイズ 厚さ×幅	長さ	kg/P		コールド	HL	#400	スリット ホット	セミ ホット	冷間 圧延	熱間圧延	
		304	316 316L							304	316 316L
	11	4,000	1.40		HL		■				
	13	//	1.65		HL						
	15	//	1.90		HL	4	■	■	●		
	16	//	2.03		HL						
	19	//	2.41		HL		■	■	●		
	20	//	2.54		HL	4	■	■		●	
	22	//	2.79		HL		■			●	
	25	//	3.17	3.19	HL	4	■	■		●	●
	30	//	3.81	3.83	HL	4	■	■		●	●
	32	//	4.08		HL	4	■	■		●	
	35	//	4.44		HL		■			●	
	38	//	4.84		HL	4	■	■		●	
	40	//	5.08	5.12	HL	4	■	■		●	●
	45	//	5.72		HL		■			●	
	50	//	6.36	6.40	HL	4	■	■		●	●
	60	//	7.60		HL		■			●	
	65	//	8.24		HL		■	■		●	
	75	//	9.52		HL		■	■		●	
	90	//	11.4		HL						
	100	//	12.7		HL		■	■			
5×	8	4,000	1.27		C						
	9	//	1.43		C						
	10	//	1.58		HL						
	12	//	1.90		HL						
	13	//	2.06		HL						
	15	//	2.38		HL	4	■	■	●		
	16	//	2.54		HL						
	19	//	3.01		HL		■	■		●	
	20	//	3.17	3.19	HL	4	■	■		●	●
	22	//	3.49		HL		■			●	
	25	//	3.96	3.99	HL	4	■	■		●	●
	30	//	4.76	4.80	HL	4	■	■		●	●
	32	//	5.08		HL	4	■			●	
	35	//	5.56		HL		■	■		●	
	38	//	6.04		HL	4	■			●	
	40	//	6.36	6.40	HL	4	■	■		●	●
	50	//	7.92	8.00	HL	4	■	■		●	●
	60	//	9.52		HL		■			●	
	65	//	10.3		HL		■	■		●	
	75	//	11.9		HL		■	■		●	
	90	//	14.3		HL		■			●	
	100	//	15.8		HL		■	■		●	
	130	//	20.6		HL						
	150	//	23.8		HL						

フラットバー SUS304・316・316L

■単位：mm

サイズ 厚さ×幅	長さ	kg/P		コールド	HL	#400	スリット ホット	セミ ホット	冷間 圧延	熱間圧延	
		304	316 316L							304	316 316L
6×9	4,000	1.71		C							
10	//	1.90			HL						
12	//	2.28			HL						
13	//	2.48			HL						
15	//	2.86			HL	4	■	■	●		
16	//	3.04			HL						
18	//	3.42			HL						
19	//	3.62			HL		■	■		●	
20	//	3.81	3.83		HL	4	■	■		●	●
22	//	4.20			HL		■			●	
25	//	4.76	4.80		HL	4	■	■		●	●
30	//	5.72	5.76		HL	4	■	■		●	●
32	//	6.08	6.12		HL	4	■	■		●	●
35	//	6.68			HL		■	■		●	
38	//	7.24	7.28		HL	4	■	■		●	●
40	//	7.60	7.68		HL	4	■	■		●	●
42	//	8.00			HL						
45	//	8.56			HL	4	■	■		●	
50	4,000	9.52	9.56		HL	4	■	■		●	●
	6,000	14.3			HL		■			●	
60	4,000	11.4			HL	4	■	■		●	
65	4,000	12.4	12.4		HL	4	■	■		●	●
	6,000	18.5			HL		■			●	
70	4,000	13.3			HL		■	■		●	
75	4,000	14.3	14.4		HL	4	■	■		●	●
	6,000	21.4			HL		■			●	
90	4,000	17.1			HL		■	■		●	
100	4,000	19.0	19.2		HL	4	■	■		●	●
	6,000	28.6			HL		■			●	
110	4,000	20.9			HL		■				
120	//	22.8			HL		■				
125	//	23.8			HL		■				
130	//	24.8			HL		■				
140	//	26.6			HL		■				
150	//	28.6			HL		■				

サイズ 厚さ×幅	長さ	kg/P		コールド	HL	#400	冷間 圧延	熱間圧延	
		304	316 316L					304	316 316L
7×20	4,000	4.44						●	
8×10	4,000	2.54		C	HL				
	16	//	4.08	C	HL			●	
25	//	6.36						●	
30	//	7.60						●	
32	//	8.12		C	HL			●	
38	//	9.64		C	HL			●	
40	//	10.2						●	
45	//	11.4						●	
50	//	12.7		C	HL			●	
65	//	16.5						●	
75	//	19.0						●	
100	//	25.4						●	
9×13	4,000	3.71		C	HL		●		
	15	//	4.28	C	HL			●	
16	//	4.56		C	HL			●	
19	//	5.44		C	HL			●	
20	//	5.72		C	HL	4		●	
22	//	6.28		C	HL			●	
25	4,000	7.12	7.20	C	HL	4		●	●
	6,000	10.7		C	HL				
30	4,000	8.56	8.60	C	HL	4		●	●
	6,000	12.8		C	HL				
32	4,000	9.12	9.20	C	HL	4		●	●
	6,000	13.7		C	HL				
35	4,000	10.0						●	
38	4,000	10.8	10.9	C	HL	4		●	●
	6,000	16.3		C	HL			●	
40	4,000	11.4		C	HL	4		●	
	6,000	17.1		C	HL				
45	4,000	12.8						●	
50	4,000	14.3	14.4	C	HL	4		●	●
	6,000	21.4		C	HL			●	
55	4,000	15.7						●	
60	//	17.1		C	HL			●	
65	4,000	18.6	18.7	C	HL	4		●	●
	6,000	27.8		C	HL			●	
75	4,000	21.4	21.6	C	HL	4		●	●
	6,000	32.1		C	HL			●	
90	4,000	25.7	25.8	C	HL			●	●
	6,000	38.6		C	HL			●	
100	4,000	28.6	28.7	C	HL			●	●
	6,000	42.8		C	HL			●	
125	4,000	35.7		C	HL			●	
	6,000	53.5						●	

※熱間圧延品はJIS G4303

◎スリットホットフラットバー

No.1コイルをスリットカットし、圧延後ショットを施したフラットバー。

◎セミホットフラットバー

No.1コイルをスリットカットし、圧延を施したフラットバー。

フラットバー

HL=HL

4=#400

C=コールド

●=酸洗仕上

フラットバー SUS304・316・316L

■単位: mm

サイズ 厚さ× 幅	長さ	kg/P		コールド	HL	#400	冷間圧延	熱間圧延	
		304	316 316L					304	316 316L
150	4,000	42.8		C	HL			●	
	6,000	64.2						●	
200	4,000	57.2		C	HL			●	
250	//	71.2		C	HL			●	
300	//	85.6		C				●	
10x	15	4,000	4.76	C	HL			●	
	19	//	6.04	C	HL			●	
	20	//	6.36	C	HL	4		●	
	25	//	7.92	C	HL	4		●	
	30	//	9.52	C	HL	4		●	
	32	//	10.2	C	HL	4		●	
	35	//	11.1					●	
	38	//	12.0	C	HL	4		●	
	40	//	12.7	C	HL	4		●	
	50	//	15.8	C	HL	4		●	●
	65	//	20.6	C	HL	4		●	
	75	//	23.8	C	HL	4		●	
	100	//	31.7	C	HL			●	●
	125	//	39.6	C	HL			●	
	150	//	47.6	C	HL			●	
	200	//	63.6	C				●	
	250	//	79.2	C				●	
	300	//	95.2	C				●	
12x	14	4,000	5.32	C					
	15	//	5.72					●	
	16	//	6.08	C	HL				
	19	//	7.24	C	HL			●	
	20	//	7.60	C	HL	4		●	
	25	//	9.52	C	HL	4		●	●
	28	//	10.6					●	
	30	//	11.4	C	HL	4		●	
	32	4,000	12.2	C	HL	4		●	●
		6,000	18.3	C	HL				
	35	4,000	13.3	C	HL			●	
	38	4,000	14.5	C	HL	4		●	●
		6,000	21.7	C	HL			●	
	40	4,000	15.2	C	HL	4		●	
		6,000	22.9	C	HL				
	45	4,000	17.1					●	
	50	4,000	19.0	C	HL	4		●	●
		6,000	28.6	C	HL			●	
	65	4,000	24.8	C	HL	4		●	●
		6,000	37.1	C	HL			●	
	70	4,000	26.6					●	
	75	4,000	28.6	C	HL	4		●	●

サイズ 厚さ× 幅	長さ	kg/P		コールド	HL	#400	冷間圧延	熱間圧延	
		304	316 316L					304	316 316L
	75	6000	42.8	C	HL			●	
	90	4,000	34.2	C	HL			●	
100	4,000	38.1	38.3	C	HL			●	●
	6,000	57.1		C	HL			●	
125	4,000	47.6		C	HL			●	
	6,000	71.4						●	
150	4,000	57.2		C	HL			●	
	6,000	85.8						●	
200	4,000	76.0		C	HL			●	
250	//	95.2		C				●	
300	//	114		C				●	
16x	19	4,000	9.64	C	HL				
	20	//	10.2	C	HL	4		●	
	25	//	12.7	C	HL	4		●	●
	30	//	15.2					●	
	32	//	16.2	C	HL	4		●	●
	35	//	17.8					●	
	38	//	19.3	C	HL	4		●	●
	40	//	20.3	C	HL			●	
50	4,000	25.4	25.5	C	HL	4		●	●
	6,000	38.0						●	
65	4,000	33.0	33.2	C	HL			●	●
	6,000	49.5						●	
75	4,000	38.1	38.3	C	HL			●	●
	6,000	57.1						●	
	90	4,000	45.6					●	
100	4,000	50.8	51.2	C	HL			●	●
	6,000	76.2						●	
125	4,000	63.6		C	HL			●	
	6,000	95.4						●	
150	4,000	76.0		C	HL			●	
	6,000	114						●	
200	4,000	102		C				●	
250	//	127		C				●	
300	//	152		C				●	
19x	25	4,000	15.1	C	HL	4		●	
	30	//	18.1					●	
	32	//	19.3	C	HL	4		●	
	35	//	21.1					●	
	38	//	22.9	C	HL	4		●	
	40	//	24.1					●	
	50	//	30.1	C	HL	4		●	●
	65	//	39.2	C	HL			●	●
	75	//	45.2	C	HL			●	●
	90	//	54.4					●	

フラットバー SUS304・316・316L

■単位：mm

サイズ 厚さ×幅	長さ	kg/P		コールド	HL	#400	冷間圧延	熱間圧延	
		304	316 316L					304	316 316L
100	4,000	60.4	60.8	C	HL			●	●
125	//	75.2		C	HL			●	
150	//	90.4		C	HL			●	
200	//	120		C				●	
250	//	151		C				●	
300	//	181		C				●	
22x 25	4,000	17.4						●	
30	//	20.9						●	
32	//	22.3		C				●	
35	//	24.4						●	
38	//	26.5		C				●	
40	//	27.9						●	
45	//	31.4						●	
50	//	34.9		C				●	
65	//	45.2		C				●	
75	//	52.4		C				●	
100	//	69.6		C				●	
125	//	87.2						●	
150	//	105						●	
200	//	140						●	
250	//	174						●	
300	//	209						●	
25x 32	4,000	25.4		C				●	
38	//	30.1		C				●	
40	//	31.7						●	
50	//	39.6		C				●	
60	//	47.6						●	
65	//	51.6		C				●	
75	//	59.6		C				●	
100	//	79.2		C				●	
125	//	99.2		C				●	
150	//	119		C				●	
200	//	158		C				●	
250	//	198						●	
300	//	238						●	
30x 50	4,000	47.6		C				●	
55	//	52.4		C				●	
65	//	62.0		C				●	
75	//	71.2		C				●	
100	//	95.2		C				●	
125	//	119						●	
150	//	143						●	
200	//	190						●	

サイズ 厚さ×幅	長さ	kg/P		コールド	HL	#400	冷間圧延	熱間圧延	
		304	316 316L					304	316 316L
250	4,000	238						●	
300	//	286						●	
35x 50	4,000	55.6		C				●	
55	//	61.2						●	
65	//	72.0		C				●	
75	//	83.2		C				●	
100	//	111		C				●	
125	//	139						●	
150	//	166						●	
40x 50	4,000	63.6						●	
65	//	82.4						●	
75	//	95.2						●	
100	//	127						●	
125	//	158						●	
150	//	190						●	
50x 65	4,000	103						●	
75	//	119						●	
100	//	158						●	
125	//	198						●	
150	//	238						●	
60x 75	4,000	143						●	
100	//	190						●	
125	//	238						●	
150	//	286						●	
65x 75	4,000	181						●	
100	//	206						●	
70x 100	4,000	222						●	
125	//	278						●	
150	//	333						●	
80x 100	4,000	254						●	
125	//	317						●	
150	//	381						●	
90x 100	4,000	286						●	
125	//	357						●	
150	//	428						●	
100x125	4,000	396						●	
150	//	476						●	

※熱間圧延品はJIS G4303